MECHANICAL					
Electric Motor		RWD (Standard Range)	RWD	AWD	
Permanent-Magnet Synchronous	Motor (PMSM)		S		
Maximum Powe kW (hp)		111 kW (149 hp)	168 kW (225 hp)	74 kW + 165 kW (320 hp)	
Maximum Torque Nm (lbft.)		350 Nm (258 lbft.)	350 Nm (258 lbft.)	605 Nm (446 lbft.)	
All Electric Range		SE Standard Range 18": estimate 240 miles			
Battery		RWD Standard Range	RWD and AWD		
Battery Type		Lithium-ion			
Voltage	Voltage 480V 697V		<i>l</i>		
Battery System Capacity		53.0 kWh	77.4 kWh		
Max Vehicle Operation Speed, Ele	ctronically Governed	115 MPH			
	AC Level II, Standard 240V (Up to 80% charge)	5 hr. 20 min	6 hr. 55 min		
Charge Time	Charging: 50kW (Up to 80% charge)	58 min	73 min		
	Rapid Charging: 350kw (Up to 80% charge)	18 min	18 min		
Charge Port		Rear Quarter / Passenger Side			
Battery Heating System Battery preconditioning function		S			

^{*} EPA 5-Cycle Test Procedure

^{*}Estimated AER

MECHANICAL					
Battery (cont.)	RWD (Standard Range)	RWD / AWD			
Power Output	173 kW	277 kW			
Energy Density (Wh/lb.)	69.1 (standard charge)	73.2 (standard charge)			
Weight (lbs.)	766.1 (not including cooling / hosepipe)	1056.5 (Long Range Standard Charge) (not including cooling / hosepipe)			
On-Board Charger (OBC)	All M	lodels			
Ultra-Fast Charger (up to 800V / 350 kW)		S			
Max Capacity (kW)	10	10.9			
Output Density (kVA/liter)	1	1.28			

MECHANICAL (cont'd)					
Electrica l System		All Models			
Non-traction electrical system		12-volt			
Transmission and Drive System		All Models			
Drive Configuration		RWD / AWD			
Transmission Type	Single-speed Reduction Gear	S			
Типэтпээютт уре	Shift-by-wire	January 1980			
Gear Ratio / Final Gear Ratio		2.263 / 4.471			
Clutch Type		Front: Dog clutch (disconnector) / Rear: none			
Lubricant Oil Capacity		Front: 3.2 liters / Rear: 3.4 liters			
Drive Mode Select (Eco → Normal → Sport → Snow → My Mode) Steering-wheel button		S			
Steering		All Models			
Rack and pinion type steering gear		S			
Motor Driven Power Steering (R-MDPS) - Power assisted, rack-mounted		S			
Overall Ratio		14.27			
Turns (lock to lock)		2.66			
Turning Diameter (curb to curb, ft.)		38.8			

MECHANICAL (cont'd)				
Brakes		All Models		
Frank	Туре	Ventilated Disc		
Front	Size (diameter x thickness, mm)	12.8" x 1.2" (Ф325x30t)		
Dogs	Туре	Solid Disc		
Rear	Size (diameter x thickness, mm)	12.8" x 0.5" (Ф325x12t)		
ABS with Electronic Brake-force Distribution (EBD)	Number of Wheels Number of Channels Number of Sensors	4 4 4		
Hillstart Assist Control (HAC)		S		
Brake Booster	Active Hydraulic Booster (Regenerative Brake)	S		
Brake Assist		S		
Electric Parking Brake	w/ Automatic Vehicle Hold	S		
Regenerative brake control paddles		S		

MECHANICAL (cont'd)			
Suspension		All Models	
Front	Туре	MacPherson strut	
FIOR	Gas Damper	S	
_	Туре	Multi-link	
Rear	Gas Damper	S	
Body/Chassis		All Models	
Туре		Unibody (Monocoque body)	
Materials Primary		Advanced High-Strength Steel; High Tensile Steel	

SAFETY/SECURITY			
Restraint Systems		ALL	
	Driver (1)	S	
	Front passenger (1)	S	
Airbags (Front - Advanced)	Occupant Classification System (OCS) Seat weight sensor and seat track sensor	S	
	Driver and front passenger side-impact FR (Thorax) (2)	S	
	Side air curtains (front and rear passengers) with rollover sensors (2)	S	
Outboard seatbelts	3-point	S	
Inboard seatbelt (rear)	3-point	S	
Adjustable front-seat shoulder belt anchors		S	
Front and Rear seatbelt pretensioners and load limiters		S	
Rear LATCH Lower Anchors and Upper Tether Anchors		S	
Power window lock-out button		S	
Rear child safety locks		S	
Active Safety			
Regenerative Braking System with Anti-lock Braking System (ABS) with 4-wheel disc brakes		S	
Electronic Stability Control (ESC) with Traction Control (TCS) and Brake Assist		S	
Vehicle Stability Management		S	
Tire Pressure Monitoring System (TPMS) with Individual Tire Indicator and Tire Fill Complete Alert		S	

SAFETY/SECURITY (cont'd)				
Active Safety (cont'd)		SE	SEL	Limited
Blind-Spot Collision Warning		S	S	S
Blind-Spot Collision Avoidance Assist		-	S	S
Surround View Monitor		-	-	S
Blind-Spot View Monitor (BVM)		-	-	S
Rear Cross-Traffic Collision Avoidance A	ssist	S	S	S
Davidia a Diatara a a Warraina	Reverse	S	S	S
Parking Distance Warning	Forward	S	S	S
Parking Collision Avoidance Assist – Rev	erse/Forward/Side(PCA-R/F/S)	-	-	S
Forward Collision-Avoidance Assist with Car/Ped/Cyclist Detection		S	-	-
Forward Collision-Avoidance Assist with Car/Ped/Cyclist Detection and Junction Turning		-	S	S
Lane Keeping Assist / Lane Following Assist		S	S	S
Intelligent Speed Limit Assist		S	S	S
Driver Attention Warning		S	S	S
Safe Exit Warning		S	S	S
Highway Driving Assist I (HDA I)		S	-	-
Highway Driving Assist II (HDA II)		-	S	S
High Beam Assist		S	S	S
Rear Occupant Alert (door logic type)		S	S	S

SAFETY/SECURITY (cont'd)					
Passive Safety	SE	SEL	Limited		
Front crumple zone	S	S	S		
2.5-MPH Bumpers	S	S	S		
Bodyside reinforcements	S	S	S		
Electronic Shift Lock System & Ignition Key Interlock - Electronic type	S	S	S		
Anti-theft System integrated with remote keyless entry and panic alarm	S	S	S		
Immobilizer	S	S	S		

DIMENSIONS/WEIGHTS/CAPACITIES					
Exterior (inches)		All			
Wheelbase		116.1			
Overall Length		191.1			
Overall Width		74.0			
Overall Height		58.9			
Tread Width (Front) - 18" / 20"		64.4 / 64.2			
Tread Width (Rear) - 18" / 20"		64.7 / 64.5			
Overhang (front/rear)		33.5 / 41.5			
Minimum Ground Clearance		5.6			
Coefficient of Drag (Cd) (lowest)		0.22			
Interior (inches)		All			
Head Room without sunroof (front / rear)		40.2 / 36.9			
Head Room with sunroof (front / rear)		38.3 / 36.9			
Leg Room – Practical (front / rear)		42.3 / 39.2			
Leg Room – Maximum (front / rear)		45.4 / 34.7			
Shoulder Room (front/rear)	-	58.0/ 57.3			
Hip Room (front/rear)		55.2 / 51.1			
Weights	RWD (Standard Range)	RWD	AWD		
Curb Weight Lightest – Heaviest (lbs.)	3,935	4,222 - 4,376	4,462 - 4,616		
GVWR RWD/AWD (lbs.)	4,894	4,894 5,313 5,556			

DIMENSIONS/WEIGHTS/CAPACITIES (cont'd)						
SAE Volume (cubic feet)	All					
Total Interior Volume			114.2			
Passenger Interior Volume			103.0			
Luggage Capacity (cuft.)			11.2			
Front Under Hood Storage Area; "Frunk" (cuft.)			0.5			
Fuel Economy / EPA Ratings	RWD (Standard Range)	RWD 18" Tire (SE)	RWD 20" Tire (SEL + Limited)	AWD 18" Tire (SE)	AWD 20" Tire (SEL & Limited)	
MPGe (City / Highway / Combined)	151/120/135	SE RWD 153/127/140	SEL & Limited RWD 129/105/117	SE AWD 130/111/121	SEL & Limited AWD 111/94/103	
Driving Range (miles combined)	240	361	305	316	270	
CO2 (grams/mile)	0	0				
Annual Fuel Cost (USD)	500	500	600	600	700	
Fuel Economy & Greenhouse Gas Rating	10	10				
Smog Rating	10 (ZEV)	10 (ZEV)				
Model Index	59	60 61 62 63				